


UHF Ceramic Tag

Product Code: U7X21211

Ceramic Tag is ideal for mount on metal application, tool tracking, IT Assets tracking etc. It is available in different chips & memory sizes.




Tag Dimensions



Electrical Specifications				
Air Interface Protocol	ISO/IEC 18000-6C, EPC Global C1G2			
Operational Frequency	865 – 868 MHz or 902 – 928 MHz			
Chip	Alien Higgs-3			
Memory Configuration	EPC-96 bits, extendible to 480bits			
	TID – 96 bits unalterable unique			
	User memory – 512 bits			
	Access password – 32 bits			
	Kill password – 32 bits			
Product Code	U7021211		U7121211	
Read range	Up to 5.0 meter on Fixed Reader	Up 1	to 3.0 meter on Fixed Reader	
Operating temperature	-40°C to +140°C			
Storage temperature	-40°C to +80°C			
Ingress protection rating	IP68			
Attachment***	Self Adhesive			
Applicable surface	Metal			
Physical and Me	echanical Specification			
Dimensions**	13 x 3.0 x 9.0 ± 0.2 mm		10 x 3.0 x 5.0 ± 0.2 mm	
Product Code	U7021211		U7121211	
Weight	2.0 g			
Encasement	Ceramic			
Quality Assurance	100% reader tested			
Chemical Resista	ance ance			
Resistant to continuous	exposure to salt water for 2 hours			
Resistant to continuous	exposure to motor oil for 2 hours			
Additionally, abrasion re	sistant against HCL and IPA			

Linear Frequency Graph



Additional Services

Pre-encoding	On request
Customization***	Logo / text printing on request

Order Information

U7021211-EU	13x9x3mm with Alien higgs-3 chip tuned at ETSI frequency
U7021211-US	13x9x3mm with Alien higgs-3 chip tuned at US frequency
U7121211-EU	10x5x3mm with Alien higgs-3 chip tuned at ETSI frequency
U7121211-US	10x5x3mm with Alien higgs-3 chip tuned at US frequency

* Actual read range may vary depending upon the reader

Other on request

Available as an option at extra cost

