


UHF Hanger Tag

Product Code: U6520314

Plastic Hanger Tag is a UHF Gen2 long range passive tag. It is specially designed for vehicle identification, And suitable for tracking items/assets in an indoor environment. Hanger Tag is ideally used for nonmetallic assets tracking as well as for pallet tracking.




Tag Dimensions



Thickness: 4mm

Electrical Specific	ations	
Air Interface Protocol	ISO/IEC 18000-6C, EPC Global C1G2	
Operational Frequency	860 – 960 MHz	
Chip**	Impinj Monza 4D	
Memory Configuration	EPC–96 bits, extendible up to 128 bits	
	TID – 96 bits unalterable unique	
	User memory – 32 bits	
	Access password – 32 bits	
	Kill password – 32 bits	
Read Range*	Up to 12 meters on fixed reader with linear Antenna	
Operating temperature	-40°C to +80°C	
Storage temperature	-40°C to +80°C	
Ingress protection rating	IP67	
Attachment	Hook provided in tag itself	
Applicable surface	Plastic, Free air	
Physical and Mechanical Specification		
Dimensions	185 x 52 x 4 ± 0.2 mm	
Colour**	Black	
Weight	32 g	
Encasement	ABS High impact	
Quality Assurance	100% reader tested	
<u>Chemical Resistance</u>		
Resistant to continuous exposure to salt water for 2 hours		
Resistant to continuous exposure to motor oil for 2 hours		
Additionally, abrasion resistant against HCL and IPA		

Linear Frequency Graph



Additional Services

Pre-encoding	On request
Customization***	Logo / text printing on request

Order Information

U6520314	With Impinj Monza 4D chip tuned at Global frequency
U6521510	With Alien higgs-3 chip tuned at Global frequency
U6521512	With Alien higgs-4 chip tuned at Global frequency

*	Actual read range may vary depending upon the reader
**	Other on request

*** | Available as an option at extra cost

