



Manufacturer of RFID tags

DATASHEET

LF Universal Tag

Tag Code: L125171

Universal Tag is ideal for asset tracking in industrial & logistics application. It is available with different Chips & memory Sizes.



Electrical Specification

Air Interface Protocol	ISO/IEC 11784/85, Read Only Mode
Operational Frequency**	125kHz (134.2kHz on request)
Chip**	EM4200
	128 bit laser programmed ROM (64 & 96 bit option available)
	Several options of data rate and data encoding <ul style="list-style-type: none">❖ Manchester 32 & 64 RF clock per bit❖ Biphas 32 & 64 RF clock per bit❖ PSK 16 RF clock per bit❖ FSK2 50RF clock per bit

Physical / Mechanical Specification

Diameter	Ø 30 mm
Thickness	3.0 mm
Weight	2.0 gm
Encasement	PC/ ABS
Color**	Black
Quality Assurance	100% reader tested

Environmental Resistance

Operating temperature	-40°C to +80°C
Storage temperature	-40°C to +80°C
Ingress protection rating	IP66
Attachment***	Adhesive
Applicable surface	Metal, Wooden, Plastic

Dimensions



Chemical Resistance

Resistant to continuous exposure to salt water for 2 hours
Resistant to continuous exposure to motor oil for 2 hours
Additionally, abrasion resistant against HCL and IPA

Additional Services

Pre-encoding	On request
Customization***	Logo / text printing on request

* Actual Read range may vary depending upon the reader and environmental factor

** Other on request

*** Available as an option at extra cost

Order Information

L125171	With EM4200
L125131	With EM4305
L125055	With NXP HitagS 256

Omnia Technologies Pvt. Ltd.

Corporate Office

Plot No 40, Sector - 18, Gurgaon, Haryana - 122 001, INDIA | +91 (124) 4101506, 4203899

Manufacturing Unit

Plot No. 68, Sector - 5, IMT Manesar, Gurgaon, Haryana - 122 050, INDIA | +91(124) 4366174, 4366411, +91 (124) 4366410 (Fax)